

CLAPET CHECK VALVE SIFT FILTER FOOT VALVE



Components	Pcs	Material
Body	1	UNI EN 12165 CW617N - DW
Plug	1	UNI EN 12165 CW617N - DW UNI EN 12164 CW617N - DW
Shutter	1	UNI EN 12165 CW617N - DW UNI EN 12164 CW617N - DW
Sift filter		Steel Inox
Filter for foot valve		UNI EN 12165 CW617N - DW UNI EN 12164 CW617N - DW
Seal		NBR 70 Sh A (ASTM D 2240)
Female thread		UNI EN ISO 228/1 (DIN 259)
Max. working temperature		90 °C
Pressure (see item table)		
Compliant fluids		Air / Water


EN OPERATING CONDITIONS

These valves are suitable for hot and cold water domestic distribution plants (Ref. Directive 2014/68/EU Art. 13) for special uses (in accordance with the pressures set out for these items and the compatibility of the different fluids with the materials making up the specific item) see chemical compatibility chart in the technical annexes.

GP 2056
CHECK VALVE



Clapet check valve, female-female, sandblasted, with rubber seal.




CODE	Size	øA mm	B mm	C mm	øD mm	gr	PN	Pack pcs/box	Master pcs/box
08028012	1/2"	46	47	8	15	166	10	60	180
08028034	3/4"	51	53	8	20	230	10	40	120
08028100	1"	61	63	10	25	350	10	20	80
08028114	1"1/4	78	70	10	33	445	10	16	64
08028112	1"1/2	93	88	10	57	730	10	8	32
08028200	2"	102	97	11	47	1045	10	4	16
08028212	2"1/2	110	120	16	55	1460	6	1	20
08028300	3"	128	135	16	70	2375	6	1	10
08028400	4"	180	180	20	90	3915	6	1	4

GP 2042
SIFT FILTER



Sift filter in stainless steel, female-female, sandblasted.




CODE	Size	A mm	gr	PN	Pack pcs/box	Master pcs/box
08029012	1/2"	57	148	20	20	160
08029034	3/4"	66	245	20	20	80
08029100	1"	80	330	20	12	72
08029114	1"1/4	92	610	20	10	40
08029112	1"1/2	101	793	20	5	25
08029200	2"	123	1370	20	2	14

GP 2052
CLASSIC FOOT VALVE



Female classic foot valve, brass filter, sandblasted.



CODE	Size	øA mm	øB mm	C mm	D mm	gr	PN	Pack pcs/box	Master pcs/box
08032034	3/4"	45	24	9	72	195	10	30	120
08032100	1"	51	28	11	80	235	10	20	80
08032114	1"1/4	61	35	13	91	385	8	12	48
08032112	1"1/2	68	40	14	108	505	8	12	48
08032200	2"	80	50	16	120	770	8	6	24
08032212	2"1/2	102	62	16	141	1330	6	1	48
08032300	3"	117	73	16	150	1615	6	1	24
08032400	4"	146	110	16	185	3195	6	1	5